



PRINCIPAL DATA:

DRIVE SYSTEM:
STATIC SCREW WITH ROTATING NUT

CAPACITY:
400KG OR 630KG

TRAVEL:
VARIABLE (UP TO A MAXIMUM OF 9000)

NO OF STOPS:
2 SHOWN (UP TO A MAXIMUM OF 6 AVAILABLE)

SUPPLY VOLTAGE:
400V 3PH 50HZ (SINGLE PHASE AVAILABLE)

RUNNING CURRENT:
4.7AMP

STARTING CURRENT:
18AMP

STANDARD COLOUR:
RAL 9003 WHITE

(OTHER RAL COLOURS AVAILABLE)

DOOR DATA:

TYPE:
GL TYPE SHOWN (ALTERNATIVES AVAILABLE)

NO OF DOORS:
2 SHOWN (UP TO A MAXIMUM OF 6 AVAILABLE)

FIRE RATING:
AVAILABLE (NOT SHOWN)

OPENING SIZE:
900 X 2000MM

DOOR FRAME:
INTEGRAL TO SHAFT ENCLOSURE

DOOR/FRAME COLOUR:
WHITE POWDER COATED RAL 9003

DOOR GLASS:
VARIABLE

CLOSER:
MANUAL TYPE SHOWN

(AUTOMATIC VERSION AVAILABLE)

FURNITURE:
FITTINGS IN ANODISED ALUMINIUM

UNLIMITED STOPS AVAILABLE (CONDITIONS APPLY)
MAXIMUM TRAVEL OF 12 METRES

The: 1000 PLATFORM, 2 STOP, LIFT ENTRY/EXIT SAME SHORT SIDE

The East Anglian Lift Co Ltd
Norwich 01603 866206

Drawn by R.PRICE	Scale NTS	Date 06/05/04
Drawing No. S A I F C _ 100	Issue 2	